

COPPER FITTINGS

PRODUCT FEATURES

Description

ÜZÜMCÜ fittings are used as an integral part of central medical gas systems in hospitals to supply medical gases to operating rooms and other related units.

Classification

ÜZÜMCÜ fittings are manufactured in accordance with the BS EN 1254-1:1998 standard. Their seamless and monoblock construction provides greater strength, durability, and user-friendly operation.

Technical Specifications

- Biostatic, preventing bacterial growth on the surface
- End connections: Copper x Copper
- Lightweight, strong, and corrosion-resistant
- Non-flammable
- Not affected by sunlight, no special storage requirements, and does not produce toxic gases in case of fire
- All connection parts contain less than 100 mg/m² (0.01 mg/cm²) of hydrocarbons on their oil-free surface
- Lightweight, strong, and corrosion-resistant



								
	90 Degree Elbow		Equal T Piece		Coupling		Reduction Piece	
Çap	Model	Order No	Model	Order No	Model	Order No	Model / Diameter	Order No
10 mm	1506.10	66.1214	1506.20	66.1223	1506.30	66.1205	1506.40 / 12x10 mm	66.1232
12 mm	1506.11	66.1215	1506.21	66.1224	1506.31	66.1206	1506.41 / 15x12 mm	66.1234
15 mm	1506.12	66.1216	1506.22	66.1225	1506.32	66.1207	1506.42 / 22x12 mm	66.1233
22 mm	1506.13	66.1217	1506.23	66.1226	1506.33	66.1208	1406.43 / 15x22 mm	66.1235
28 mm	1506.14	66.1218	1506.24	66.1227	1506.34	66.1209	1406.44 / 15x28 mm	66.1236
35 mm	1506.15	66.1219	1506.25	66.1228	1506.35	66.1210	1406.45 / 22x28 mm	66.1237
42 mm	1506.16	66.1220	1506.26	66.1229	1506.36	66.1211	1406.46 / 22x35 mm	66.1238
54 mm	1506.17	66.1221	1506.27	66.1230	1506.37	66.1212	1506.51 / 54x22 mm	66.1243
76 mm	1506.18	66.1222	1506.28	66.1231	1506.38	66.1213	1506.52 / 54x28 mm	66.1244
							1506.50 / 54x35 mm	66.1242
							1506.53 / 76x54 mm	66.1245
							1506.47 / 35x28 mm	66.1239
							1506.48 / 35x42 mm	66.1240
							1506.49 / 54x42 mm	66.1241