

# COPPER TUBES



## PRODUCT FEATURES

### Description

ÜZÜMCÜ Medical Copper Tubes are installed as part of the system to provide gas transmission to operating rooms and other related units in hospitals' central medical gas systems.

### Classification

ÜZÜMCÜ Medical Copper Tubes are designed and manufactured in accordance with BS EN 1057 and BS 2871 standards, as well as the requirements specified in HTM 2022 and NHS engineering specifications.

### Technical Specifications

- Provides pipeline solutions for medical gas systems.
- Medical copper pipes are degreased and marked in accordance with the EN 13348 standard.
- Copper pipes are available in lengths of 4 meters, each with a red cap.
- The system is designed to meet the requirements of the medical gas industry.
- Copper pipes are available in 4-meter lengths, each with a red cap.
- We have stock available for quick delivery.
- Pipes are shipped in special wooden boxes for safe transport.

| Model   | Order No | Diameter | Wall Thickness | Working Pressur |
|---------|----------|----------|----------------|-----------------|
| 1066.10 | 66.1180  | 10 mm    | 0,6 mm         | 84 bar          |
| 1006.10 | 66.1181  | 10 mm    | 1,0 mm         | 84 bar          |
| 1066.12 | 66.1182  | 12 mm    | 0,6 mm         | 77 bar          |
| 1006.12 | 66.1184  | 12 mm    | 1,0 mm         | 77 bar          |
| 1076.15 | 66.1185  | 15 mm    | 0,7 mm         | 63 bar          |
| 1006.15 | 66.1188  | 15 mm    | 1,0 mm         | 63 bar          |
| 1006.22 | 66.1189  | 22 mm    | 1,0 mm         | 58 bar          |
| 1006.28 | 66.1193  | 28 mm    | 1,0 mm         | 51 bar          |
| 1156.28 | 66.1194  | 28 mm    | 1,5 mm         | 51 bar          |
| 1006.35 | 66.1196  | 35 mm    | 1,0 mm         | 40 bar          |
| 1156.35 | 66.1197  | 35 mm    | 1,5 mm         | 40 bar          |
| 1006.42 | 66.1198  | 42 mm    | 1,0 mm         | 42 bar          |
| 1156.42 | 66.1199  | 42 mm    | 1,5 mm         | 42 bar          |
| 1156.54 | 66.1200  | 54 mm    | 1,5 mm         | 27 bar          |
| 1206.54 | 66.1201  | 54 mm    | 2,0 mm         | 27 bar          |
| 1156.76 | 66.1202  | 76 mm    | 1,5 mm         | 29 bar          |
| 1206.76 | 66.1203  | 76 mm    | 2,0 mm         | 29 bar          |